

Application
Household Electrical Appliances, Laminator, Auto Control Machine Spotlight, etc.



Safety	
Insulation resistance	DC 500V 100M ohms
Insulation strength	AC1500V, 50Hz/min(220V motor)
Insulation class	E(105°C) / B(130°C)
Environment	Temp.-10°C~+40°C / Humidity: <85
Certification	CE RoHS CCC

Specification										
Model	Output speed (rpm)	Output Torque (kg.cm / lb.in)			Voltage (V.AC)	Current (A)	Frequency (Hz)	Input Power (W)	Noise (dB)	Rotation
		S1 continuous	S2 15 minutes	S2 5 minutes						
S593-50-05B	5	50/43.5	80 / 69.6	100 / 87	24 ***** 110 ***** 220	<0.3 ***** <0.065 ***** <0.032	50/60Hz	<16	<40	CW / CCW / Bi-directional
S593-25-10	10	25 / 21.8	45 / 39.2	52 / 45.2						
S593-20-12	12	20 / 17.4	37 / 32.2	43 / 37.4						
S593-16-15	15	16 / 13.9	29 / 43.5	35 / 30.5						
S593-12-20	20	12/ 10.4	22 / 19.1	26 / 22.6						
S593-08-30	30	8 / 7	15/ 13	17.5 / 15.2						
S593-04-60	60	4/3.5	7/6	8.8/7.7						
S593-03-98	98	2.5 / 2.18	4.5/ 3.9	5.3 / 4.6						

Note: Above datas are from motors under 50Hz. If under 60Hz, Speed*1.2 , Torque/1.2
Other speed and torque needed, please contact our sale department

